		Page: 1
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE  NP75601		Version: 1.1

29 CFR 1910.1200 (OSHA HazCom 2012)

## SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

### Product identifier

Trade name : NAPA® MPURP WHEEL BEARING GREASE  
GREASE

### Recommended use of the chemical and restrictions on use

<b>Details of the supplier of the safety data sheet</b>  Valvoline LLC 3499 Blazer Parkway Lexington, KY 40509 United States of America  SDS@valvoline.com	<b>Emergency telephone number</b> 1-800-VALVOLINE  <b>Regulatory Information Number</b> 1-800-TEAMVAL  <b>Product Information</b> 1-800-TEAMVAL
---	--

## SECTION 2. HAZARDS IDENTIFICATION

### GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

### Other hazards

None known.


## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

### Hazardous components


Chemical Name	CAS-No.	Classification	Concentration (%)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	Asp. Tox. 1; H304	74.99

		Page: 2
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

ASPHALT	8052-42-4	Not a hazardous substance or mixture.	24.99
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	Not a hazardous substance or mixture.	9.99

#### SECTION 4. FIRST AID MEASURES

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.  
If unconscious place in recovery position and seek medical advice.  
If symptoms persist, call a physician.
- In case of skin contact : First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
- In case of eye contact : Remove contact lenses.  
Protect unharmed eye.
- If swallowed : Do not give milk or alcoholic beverages.  
Never give anything by mouth to an unconscious person.  
If symptoms persist, call a physician.
- Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.
- Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:  
stomach or intestinal upset (nausea, vomiting, diarrhea)  
irritation (nose, throat, airways)

		Page: 3
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE  NP75601		Version: 1.1

Notes to physician : No hazards which require special first aid measures.

---


## SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
 Water spray  
 Foam  
 Carbon dioxide (CO<sub>2</sub>)  
 Dry chemical
- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : carbon dioxide and carbon monoxide  
 sulfur oxides  
 Hydrocarbons  
 Aldehydes  
 Ketones  
 Nitrogen oxides (NO<sub>x</sub>)  
 Sulphur oxides
- Specific extinguishing methods :  
  
 Product is compatible with standard fire-fighting agents.
- Further information : Standard procedure for chemical fires.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

---

## SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
- Environmental precautions : Prevent further leakage or spillage if safe to do so.
- Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).  
 Keep in suitable, closed containers for disposal.
- Other information : Comply with all applicable federal, state, and local regulations.

		Page: 4
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

## SECTION 7. HANDLING AND STORAGE


- Advice on safe handling : Smoking, eating and drinking should be prohibited in the application area.  
For personal protection see section 8.
- Conditions for safe storage : Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : No materials to be especially mentioned.

## SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0	REL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA_TRANS
		REL	5 mg/m <sup>3</sup> Mist.	NIOSH/GUIDE
		STEL	10 mg/m <sup>3</sup> Mist.	NIOSH/GUIDE
		REL	5 mg/m <sup>3</sup> Mist.	OSHA_TRANS
		TWA	5 mg/m <sup>3</sup> Mist.	Z1A
ASPHALT	8052-42-4	TWA	400 ppm 1,600 mg/m <sup>3</sup>	Z1A
		TWA	0.5 mg/m <sup>3</sup> Inhalable fraction. (as benzene solubles)	ACGIH
		Ceil_Time	5 mg/m <sup>3</sup> Fume.	NIOSH/GUIDE
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA	64742-52-5	REL	500 ppm 2,000 mg/m <sup>3</sup>	OSHA_TRANS
		REL	5 mg/m <sup>3</sup> Mist.	NIOSH/GUIDE
		STEL	10 mg/m <sup>3</sup> Mist.	NIOSH/GUIDE
		REL	5 mg/m <sup>3</sup> Mist.	OSHA_TRANS

**Engineering measures** : General room ventilation should be adequate for normal

		Page: 5
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.


**Personal protective equipment**

- Respiratory protection : No personal respiratory protective equipment normally required.
  
- Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.
  
- Skin and body protection : Wear as appropriate:  
Safety shoes  
Wear resistant gloves (consult your safety equipment supplier).
  
- Hygiene measures : General industrial hygiene practice.

---

**SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES**

- Appearance : gel
- Physical state : liquid
- Colour : red
- Odour : No data available
- Odour Threshold : No data available
- pH : No data available
- Melting point/freezing point : No data available
- : 640 °F / 338 °C
- Flash point : 471 °F / 244 °C
- Evaporation rate : No data available
- Flammability (solid, gas) : No data available
- Upper explosion limit : No data available
- Lower explosion limit : No data available

		Page: 6
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

Vapour pressure : < 0.01 mmHg (20 °C)

Relative vapour density : No data available

Relative density : 0.95 (15.6 °C)

Density : 0.90 g/cm<sup>3</sup> (20 °C)

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 315 °C

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : > 20.5 mm<sup>2</sup>/s (40 °C)

Oxidizing properties : No data available

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : No decomposition if stored and applied as directed.


Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Product will not undergo hazardous polymerization.

Incompatible materials : Strong oxidizing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide  
Hydrocarbons  
Sulphur oxides

		Page: 7
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

## SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure : Inhalation  
Skin contact  
Eye Contact  
Ingestion

### Acute toxicity

Not classified based on available information.

#### Product:

Acute oral toxicity : Acute toxicity estimate (Rat): 3,019 mg/kg

Acute dermal toxicity : Acute toxicity estimate (Rabbit): 169,492 mg/kg

#### Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Acute oral toxicity : LD 50 (Rat): > 5 g/kg

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: Not classified as acutely toxic by inhalation under GHS.

Acute dermal toxicity : LD 50 (Rabbit): > 2,000 mg/kg

Assessment: Not classified as acutely toxic by dermal absorption under GHS.

Remarks: No mortality observed at this dose.

### Skin corrosion/irritation

Not classified based on available information.

#### Product:

Result: Not irritating to skin

Result: Repeated exposure may cause skin dryness or cracking.


#### Components:

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Result: Mildly irritating to skin

ASPHALT:

Result: Not irritating to skin

		Page: 8
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE  NP75601		Version: 1.1

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:  
 Species: Rabbit  
 Result: Not irritating to skin

**Serious eye damage/eye irritation**

Not classified based on available information.

**Product:**

Result: Not irritating to eyes

Remarks: Unlikely to cause eye irritation or injury.

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:  
 Result: Mildly irritating to eyes

**ASPHALT:**

Result: Possibly irritating to eyes

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:  
 Species: Rabbit  
 Result: Mildly irritating to eyes

**Respiratory or skin sensitisation**

Skin sensitisation: Not classified based on available information.  
 Respiratory sensitisation: Not classified based on available information.

**Components:**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:  
 Species: Guinea pig  
 Assessment: Does not cause skin sensitisation.  
 Method: OECD Test Guideline 406

**Germ cell mutagenicity**

Not classified based on available information.

**Carcinogenicity**

Not classified based on available information.

**Reproductive toxicity**

Not classified based on available information.

**STOT - single exposure**

Not classified based on available information.

**STOT - repeated exposure**

Not classified based on available information.

**Aspiration toxicity**

Not classified based on available information.


**Product:**

No aspiration toxicity classification

**Components:**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:  
 May be fatal if swallowed and enters airways.



		Page: 9
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

**Further information**

**Product:**

Remarks: No data available

**Carcinogenicity:**

**IARC**

Group 2B: Possibly carcinogenic to humans

ASPHALT

8052-42-4

**OSHA**

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

**NTP**

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

---

**SECTION 12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 203


Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l  
 End point: Growth inhibition  
 Exposure time: 72 h  
 Test Type: static test  
 Test substance: WAF  
 Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l  
 Exposure time: 21 d  
 Test Type: semi-static test  
 Test substance: WAF  
 Method: OECD Test Guideline 211

**Persistence and degradability**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTA:

		Page: 10
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE  NP75601		Version: 1.1

Biodegradability : Result: Inherently biodegradable  
 Biodegradation: 31 %  
 Exposure time: 28 d  
 Method: OECD Test Guideline 301F

**Bioaccumulative potential**

No data available

**Mobility in soil**

No data available

**Other adverse effects**

No data available

**Product:**

Additional ecological information : No data available

**SECTION 13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

General advice : Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.

**SECTION 14. TRANSPORT INFORMATION**

**International transport regulations**

**REGULATION**

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

**U.S. DOT - ROAD**

Not dangerous goods
---------------------


**CFR\_RAIL\_C**

Not dangerous goods
---------------------

**U.S. DOT - INLAND WATERWAYS**

Not dangerous goods
---------------------

**TDG\_ROAD\_C**

		Page: 11
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

Not dangerous goods
---------------------

**TDG\_RAIL\_C**

Not dangerous goods
---------------------

**TDG\_INWT\_C**

Not dangerous goods
---------------------

**INTERNATIONAL MARITIME DANGEROUS GOODS**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO**

Not dangerous goods
---------------------

**INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER**

Not dangerous goods
---------------------

**MX\_DG**

Not dangerous goods
---------------------

**\*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


**SECTION 15. REGULATORY INFORMATION**

**SARA 311/312 Hazards** : No SARA Hazards

**SARA 313 Component(s)SARA 313** : This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

**California Prop 65** Proposition 65 warnings are not required for this product based on the results of a risk assessment.

**The components of this product are reported in the following inventories:**

		Page: 12
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

- TSCA : On TSCA Inventory
- AUSTR : On the inventory, or in compliance with the inventory
- DSL : All components of this product are on the Canadian DSL.
- ENCS : On the inventory, or in compliance with the inventory
- KECL : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory


**Inventories**

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECL (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

**SECTION 16. OTHER INFORMATION**

**Further information**

Revision Date: 07/31/2016

<p><b>NFPA:</b></p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health      Instability</p> <p>Special hazard.</p> </div>	<p><b>HMIS III:</b></p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white; text-align: center;"><b>HEALTH</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: red; color: white; text-align: center;"><b>FLAMMABILITY</b></td> <td style="text-align: center;"><b>1</b></td> </tr> <tr> <td style="background-color: yellow; text-align: center;"><b>PHYSICAL HAZARD</b></td> <td style="text-align: center;"><b>0</b></td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	<b>HEALTH</b>	<b>1</b>	<b>FLAMMABILITY</b>	<b>1</b>	<b>PHYSICAL HAZARD</b>	<b>0</b>
<b>HEALTH</b>	<b>1</b>						
<b>FLAMMABILITY</b>	<b>1</b>						
<b>PHYSICAL HAZARD</b>	<b>0</b>						


**NFPA Flammable and Combustible Liquids Classification**

Combustible Liquid Class IIIB

**Full text of H-Statements referred to under sections 2 and 3.**

H304                      May be fatal if swallowed and enters airways.

Sources of key data used to compile the Safety Data Sheet  
Valvoline internal data including own and sponsored test reports

		Page: 13
<b>SAFETY DATA SHEET</b>		Revision Date: 07/31/2016
		Print Date: 9/27/2016
		SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE		Version: 1.1
NP75601		

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-825-8654).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists  
 BEI : Biological Exposure Index  
 CAS : Chemical Abstracts Service (Division of the American Chemical Society).  
 CMR : Carcinogenic, Mutagenic or Toxic for Reproduction  
 FG : Food grade  
 GHS : Globally Harmonized System of Classification and Labeling of Chemicals.  
 H-statement : Hazard Statement  
 IATA : International Air Transport Association.  
 IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization  
 ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"  
 IMDG : International Maritime Code for Dangerous Goods  
 ISO : International Organization for Standardization  
 logPow : octanol-water partition coefficient  
 LCxx : Lethal Concentration, for xx percent of test population  
 LDxx : Lethal Dose, for xx percent of test population.  
 ICxx : Inhibitory Concentration for xx of a substance  
 Ecxx : Effective Concentration of xx  
 N.O.S.: Not Otherwise Specified  
 OECD : Organization for Economic Co-operation and Development  
 OEL : Occupational Exposure Limit  
 P-Statement : Precautionary Statement  
 PBT : Persistent , Bioaccumulative and Toxic  
 PPE : Personal Protective Equipment  
 STEL : Short-term exposure limit  
 STOT : Specific Target Organ Toxicity  
 TLV : Threshold Limit Value  
 TWA : Time-weighted average  
 vPvB : Very Persistent and Very Bioaccumulative  
 WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act  
 DOT : Department of Transportation  
 FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act  
 HMIRC : Hazardous Materials Information Review Commission  
 HMIS : Hazardous Materials Identification System  
 NFPA : National Fire Protection Association  
 NIOSH : National Institute for Occupational Safety and Health  
 OSHA : Occupational Safety and Health Administration

	Page: 14
<b>SAFETY DATA SHEET</b>	Revision Date: 07/31/2016
	Print Date: 9/27/2016
	SDS Number: R0172170
NAPA® MPURP WHEEL BEARING GREASE GREASE  NP75601	Version: 1.1

PMRA : Health Canada Pest Management Regulatory Agency  
 RTK : Right to Know  
 WHMIS : Workplace Hazardous Materials Information System