



Product Safety Data Sheet (PSDS)



US Office

P&G
 Berkshire Corporate Park
 14 Research Drive
 Bethel, CT USA 06401
 (203) 796-4000

Canadian Office

P&G
 4711 Yonge Street
 Toronto, Ontario
 Canada M2N 6K8
 (416) 730-4711

SECTION I - PRODUCT IDENTIFICATION



Representative Product Image/
 Packaging

The battery products referenced in this PSDS document are consumer products. Under OSHA regulations, batteries are considered “articles” and are not subject to the OSHA Hazard Communication Standard MSDS/SDS requirements which apply for “hazardous chemicals in the workplace.” Additionally, batteries are considered “articles” under the Global Harmonized System and are exempted from the GHS labeling and SDS classification criteria. This PSDS document is provided as service in response to requests for information on battery use, safety and regulatory compliance.

| Duracell Designation | Size | Nominal Voltage |
|--|------|-----------------|
| PC 2400 | AAA | 1.5V |
| PC 1500 | AA | 1.5V |
| PC 1500 | C | 1.5V |
| PC 1300 | D | 1.5V |
| PC 1604 | 9V | 9V |
| Alkaline lantern covered by this PSDS : PC 908, PC915, PC918 | | |
| Consumer Relations 1-800-551-2355 (9 :00 AM – 5 :00 PM EST) | | |

SECTION II - HAZARDS IDENTIFICATION

CAUTION: May batteries may explode or leak, and cause burn injury, if recharged, disposed of in fire, mixed with a different battery type, inserted backwards or disassembled. Replace all used batteries at the same time. Do not carry batteries loose in your pock or purse. Do not remove the battery label. Keep small batteries (i.e., AAA) away from children. If swallowed, consult a physician at once. **For information on treatment, call (202) 625-3333 collect.**

SECTION III - COMPOSITION AND INGREDIENTS

The chemicals and metals in this product are contained in a sealed can. Exposure to the contents will not occur unless the battery leaks, is exposed to high temperatures or is mechanically, physically, or electrically abused. Hazardous Ingredients as defined by OSHA, 29 CFR 1910.1200. and/or WHMIS under the HPA:

| <u>Chemical Name</u> | <u>CAS No.</u> | <u>Composition Range</u> | <u>LD50/LC50</u> | <u>Exposure Limits</u> |
|---------------------------------|-------------------------|--------------------------|----------------------------|--|
| Manganese Dioxide | 1313-13-9 | 35-40% | LD50 oral rat > 3478 mg/kg | 5 mg/m ³ Ceiling OSHA PEL 0.2 mg/m ³ TWA ACGIH TLV |
| Zinc | 7440-66-6 | 10-25% | | None established for zinc metal |
| Potassium Hydroxide | 1310-58-3 | 5-10% | LD50 oral rat 273 mg/kg | 2 mg/m ³ Ceiling ACGIH TLV |
| Graphite (natural or synthetic) | 7782-42-5; 7440-44-0 | 1-5% | | Natural: 15 mppcf TWA OSHA PEL 2 mg/m ³ TWA (respirable dust) ACGIH TLV; Synthetic: 5 mg/m ³ TWA (respirable dust), 15 mg/m ³ TWA (total dust) OSHA PEL 2 mg/m ³ |

SECTION IV – FIRST AID INFORMATION

Damaged battery will release concentrated potassium hydroxide, which is caustic.

Ingestion: Do not induce vomiting. Seek medical attention immediately. **CALL NATIONAL BATTERY INGESTION HOTLINE at (202)-625-3333 collect, day or night.**

Eye Contact: Immediately flush eyes thoroughly with water for at least 15 minutes. Seek medical attention if irritation persists.

Skin Contact: Remove contaminated clothing and wash skin with soap and water. If irritation persists, seek medical attention.

Inhalation: Move to fresh air. If irritation persists, seek medical attention.

SECTION V - FIRE FIGHTING INFORMATION

Hazardous Combustion Products: Thermal degradation may produce hazardous fumes of zinc and manganese; hydrogen gas, caustic vapors of potassium hydroxide and other toxic by-products.

Extinguishing Media: Use any extinguishing media that is appropriate for the surrounding area.

Protection of Firefighters:

Specific Hazards Arising from the Material: Batteries may burst and release hazardous decomposition products when exposed to a fire situation.

Protective Equipment and Precautions for Firefighters: Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing.

SECTION VI - ACCIDENTAL RELEASE MEASURES

Notify safety personnel of large spills. Caustic potassium hydroxide may be released from leaking or ruptured batteries. Clean-up personnel should wear appropriate clothing to avoid eye and skin contact and inhalation of vapors and fumes. Ventilate area. Carefully collect batteries and place in an appropriate container for disposal.

SECTION VII – HANDLING AND STORAGE

Precautions To Be Taken in Handling: Avoid mechanical or electrical abuse. DO NOT short circuit or install incorrectly. Batteries may rupture or vent if disassembled, crushed, recharged or exposed to high temperatures. Install batteries in accordance with equipment instructions.

Precautions To Be Taken in Storage: Store batteries in a dry place at normal room temperature. Do not refrigerate – this will not make them last longer.

SECTION VIII - EXPOSURE CONTROLS / PERSONAL PROTECTION

NOT APPLICABLE – Finished consumer product

SECTION IX - PHYSICAL AND CHEMICAL PROPERTIES

Appearance (color, physical form, shape): Finished consumer product – cylindrical battery with Duracell® label

Volatile Organic Compound (VOC): Not applicable - Product not regulated for VOC Content at State or Federal level

SECTION X - STABILITY AND REACTIVITY

Finished consumer product – stable under normal conditions of use. Contents are incompatible with strong oxidizing agents. Do not heat, crush, disassemble, short circuit or recharge.

SECTION XI - TOXICOLOGICAL INFORMATION

This battery product is a finished consumer product. It is classified as an “article” and exempt under the federal OSHA Hazard Communication standard.

Chronic Effects: No chronic health effects reported.

Target Organs: No target organs reported.

Carcinogenicity: This finished consumer product is not carcinogenic.

SECTION XII - ECOLOGICAL INFORMATION

No eco-toxicity data are available. This product is not expected to present an environmental hazard. Duracell alkaline batteries do not contain any added mercury, cadmium or lead.

SECTION XIII - DISPOSAL CONSIDERATIONS

Waste Disposal Method: Dispose of in compliance with federal, state/provincial and local regulations.
Non-Household Setting (US Federal): Alkaline batteries covered by this PSDS, in their original form (finished consumer product), when disposed of as waste, are considered **non-hazardous** waste according to Federal RCRA regulation (40 CFR 261).
Non-Household Setting (California): None
Household Use: Alkaline batteries can be safely disposed of with normal household waste. Do not accumulate large quantities used batteries for disposal as accumulation could cause batteries to short-circuit. Do not incinerate.

SECTION XIV - TRANSPORT INFORMATION

Alkaline batteries (sometimes referred to as “Dry cell” or “household” batteries) are not listed or regulated as dangerous goods under the IATA Dangerous Goods Regulations, ICAO Technical Instructions, IMDG Code, UN Model Regulations or U.S. hazardous regulations (49CFR). However, special regulatory provisions apply that require batteries to be packaged in a manner that prevents the generation of a dangerous quantity of heat and short circuits. Product shipped in its original unopened Duracell packaging is compliant with the packaging special provisions.

Ground Transport (US DOT): 49 CFR172.102 Special Provision 130

Air Transport (IATA)/ICAO: Special Provision A123

Marine/Water Transport (IMDG): NONE

SECTION XV - REGULATORY INFORMATION

United States:

OSHA: The finished alkaline battery product is considered an article and not covered by the OSHA Hazard Communication Standard, 29 CFR 1910.1200

CPSIA 2008: Alkaline batteries are exempt. See CPSC Exemption Letter posted on P&G web site.

EPA Mercury Containing and Rechargeable Battery Management Act of 1996: Compliant

EPA TSCA: All intentionally-added components of this product are listed on the US TSCA Inventory.

EPA SARA 313/302/304/311/312 chemicals: Manganese compounds 35-40%; Zinc 10-25%

California: This product has been evaluated and does not require warning labeling under California Proposition 65.

State Right-to-Know and CERCLA: The following ingredients present in the finished product are listed on state right-to-know lists or state worker exposure lists:

| Ingredient | CAS # | Level | CERCLA RQ | State | | | | |
|---------------------|------------------------|--------|-----------|-------|----|----|----|----|
| | | | | IL | MA | NJ | PA | RI |
| Manganese Dioxide | 1313-13-9 | 35-40% | None | Y | Y | N | Y | Y |
| Zinc | 7440-66-6 | 10-25% | 1000 lbs | Y | Y | Y | Y | N |
| Potassium Hydroxide | 1310-58-3 | 5-10% | 1000 lbs | Y | Y | Y | Y | Y |
| Graphite | 7782-42-5 7440-44-0 | 1-5% | None | Y | Y | N | Y | Y |

Canada:

All ingredients are CEPA approved for import to Canada by Procter & Gamble. This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and this MSDS contains all information required by the Controlled Products Regulations.

SECTION XVI - OTHER INFORMATION

P&G Hazard Rating: Health: 0 4=EXTREME
 Flammability: 0 3=HIGH
 Reactivity: 0 2=MODERATE
 1=SLIGHT
 0=NOT SIGNIFICANT

Hazard Ratings are supplied for use only in connection with occupational safety and health.

DISCLAIMER: This PSDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by Procter & Gamble to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design the appropriate protective mechanisms to prevent employee exposures, property damage or release to the environment. Procter & Gamble assumed no responsibility for injury to the recipient or third persons or for any damage to any property resulting from misuse of the product.