

Issue date 08-Jan-2019

Revision date 08-Jan-2019

Revision Number 1

1. IDENTIFICATION

Product identification

Product identifier Lawson Ceiling Tile Paint - New White
 Other means of identification 96214
 Recommended use Coating
 Restrictions on use For industrial use only

Supplier

Corporate Headquarters:
 Lawson Products, Inc.
 8770 W. Bryn Mawr Ave., Suite 900
 Chicago, IL 60631
 (866) 837-9908

Canadian Distribution Center:
 Lawson Canada
 7315 Rapistan Court
 Mississauga, ON L5N 5Z4
 (800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Serious eye damage/eye irritation	Category 2B
Reproductive toxicity	Category 2
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Symbol



Signal word

DANGER

Hazard statements

H222 - Extremely flammable aerosol
 H280 - Contains gas under pressure; may explode if heated
 H320 - Causes eye irritation

H361 - Suspected of damaging fertility or the unborn child
 H335 - May cause respiratory irritation
 H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements

General

P101 - If medical advice is needed, have product container or label at hand
 P102 - Keep out of reach of children
 P103 - Read label before use.

Prevention

P201 - Obtain special instructions before use
 P202 - Do not handle until all safety precautions have been read and understood
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 - Do not spray on an open flame or other ignition source
 P251 - Pressurized container: Do not pierce or burn, even after use
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray
 P264 - Wash hands thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area

Response

General

P312 - Call a POISON CENTER or doctor if you feel unwell

Eyes

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P337 + P313 - If eye irritation persists: Get medical advice/attention

Inhalation

P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P312 - Call a POISON CENTER or doctor if you feel unwell

Fire

Not available

Spill

Not available

Storage

P403 - Store in a well-ventilated place
 P405 - Store locked up
 P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

Disposal

P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazard(s) Not Otherwise Classified (HNOC)

Not available.

Physical Hazards Not Otherwise Classified (PHNOC)

Not available.

Unknown acute toxicity

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition

Mixture.

Chemical name	CAS-No	Weight %
Propane	74-98-6	10-30

Toluene	108-88-3	10-30
N-Butane	106-97-8	7-13
Titanium dioxide	13463-67-7	7-13
Naphtha, petroleum, hydrotreated light	64742-49-0	3-7
Calcium Carbonate	1317-65-3	3-7
Isobutyl acetate	110-19-0	1-5
Mineral Spirits	64742-47-8	1-5
Xylene (mix)	1330-20-7	1-5
PM Acetate	108-65-6	1-5

The exact percentage (concentration) of composition has been withheld as a trade secret

4. FIRST-AID MEASURES

Necessary first-aid measures

Inhalation	Move to fresh air. If symptoms persist, call a physician.
Ingestion	Rinse mouth. Drink plenty of water. Do NOT induce vomiting.
Skin contact	Remove and wash contaminated clothing before re-use. Wash area thoroughly with soap and water.
Eye contact	Rinse thoroughly with plenty of water, also under the eyelids. Seek medical attention.
Most important symptoms (acute)	Dizziness.
Most important symptoms (over-exposure)	Not available.
Indication of any immediate medical attention and special treatment needed	Not available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	Carbon dioxide (CO ₂). Extinguishing powder. Water spray. Water spray for large fires.
Unsuitable extinguishing media	Not available.
Specific hazards	Can form explosive gas-air mixtures.
Special protective equipment for fire-fighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	Wear personal protective equipment. Keep unnecessary and unprotected personnel from entering the area. Use respiratory protective device against the effects of fumes/dust/aerosol.
Methods and materials for containment and cleaning up	Ensure adequate ventilation. Dispose of all product, residues and clean-up materials in accordance with local, state, and federal regulations.

7. HANDLING AND STORAGE

Precautions for safe handling

Use only in a well ventilated area. Keep away from heat and sources of ignition. Keep away from direct sunlight. Store locked up.

Conditions for safe storage, including any incompatibilities

Protect from sunlight. Store in a well-ventilated place. Do not allow to freeze.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	ACGIH OEL (TWA)	NIOSH - TWA
Propane	1000 ppm TWA 1800 mg/m ³ TWA	-	1000 ppm TWA 1800 mg/m ³ TWA
Toluene	300 ppm Ceiling 200 ppm TWA	20 ppm TWA	150 ppm STEL 560 mg/m ³ STEL 100 ppm TWA 375 mg/m ³ TWA
N-Butane	-	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA
Titanium dioxide	15 mg/m ³ TWA	10 mg/m ³ TWA	-
Naphtha, petroleum, hydrotreated light	-	-	350 mg/m ³ TWA 350 mg/m ³ TWA
Calcium Carbonate	15 mg/m ³ TWA 5 mg/m ³ TWA	-	10 mg/m ³ TWA 5 mg/m ³ TWA
Isobutyl acetate	150 ppm TWA 700 mg/m ³ TWA	150 ppm STEL 50 ppm TWA	150 ppm TWA 700 mg/m ³ TWA
Mineral Spirits	-	-	-
Xylene (mix)	100 ppm TWA 435 mg/m ³ TWA	150 ppm STEL 100 ppm TWA	-
PM Acetate	-	-	-

Appropriate engineering controls

A safety shower and eye wash station should be available for emergency use. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment**Eye protection**

Tightly fitting safety goggles.

Skin and body protection

Wear adequate protective clothes. Nitrile gloves are recommended.

Respiratory protection

A respirator is generally not necessary when using this product outdoors or in a large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Wash hands before breaks and immediately after handling the product. Remove and wash contaminated clothing before re-use. Store protective clothing separately. Do not eat or drink while working.

Canadian Province Occupational Exposure Limits

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland & Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL

Chemical name	Alberta OEL	British Columbia OEL	Manitoba OEL	New Brunswick - OEL	Newfoundland and Labrador - OEL	Nova Scotia - OEL	Ontario OEL	Prince Edward Island - OEL	Quebec OEL	Saskatchewan - OEL
Propane	1000 ppm TWA	1000 ppm TWA 1000 ppm TWA	-	-	-	-	-	-	1000 ppm TWAEV 1800 mg/m ³ TWAEV	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA
Toluene	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	50 ppm TWAEV 188 mg/m ³ TWAEV	60 ppm STEL 50 ppm TWA
N-Butane	1000 ppm TWA	750 ppm STEL 600 ppm TWA 1000 ppm TWA	1000 ppm STEL	800 ppm TWA 1900 mg/m ³ TWA	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	1000 ppm STEL	800 ppm TWAEV 1900 mg/m ³ TWAEV	1250 ppm STEL 1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
Titanium dioxide	10 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWA	10 mg/m ³ TWAEV	20 mg/m ³ STEL 10 mg/m ³ TWA
Naphtha, petroleum, hydrotreated light	-	-	-	-	-	-	-	-	-	-
Calcium Carbonate	10 mg/m ³ TWA	20 mg/m ³ STEL 10 mg/m ³ TWA 3 mg/m ³ TWA	-	10 mg/m ³ TWA	-	-	-	-	10 mg/m ³ TWAEV	20 mg/m ³ STEL 10 mg/m ³ TWA
Isobutyl acetate	150 ppm TWA 713 mg/m ³ TWA	150 ppm TWA	50 ppm TWA 150 ppm STEL	150 ppm TWA 713 mg/m ³ TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	150 ppm STEL 50 ppm TWA	150 ppm TWA	150 ppm STEL 50 ppm TWA 50 ppm TWA	150 ppm TWAEV 713 mg/m ³ TWAEV	188 ppm STEL 150 ppm TWA
Mineral Spirits	-	200 mg/m ³ TWA	-	-	-	-	-	-	-	-
Xylene (mix)	150 ppm STEL 651 mg/m ³ STEL 100 ppm TWA 434 mg/m ³ TWA	150 ppm STEL 100 ppm TWA	100 ppm TWA 150 ppm STEL	150 ppm STEL 651 mg/m ³ STEL 100 ppm TWA 434 mg/m ³ TWA	150 ppm STEL 100 ppm TWA	150 ppm STEL 100 ppm TWA	150 ppm STEL 100 ppm TWA	150 ppm STEL 100 ppm TWA	150 ppm STEV 651 mg/m ³ STEV 100 ppm TWAEV 434 mg/m ³ TWAEV	150 ppm STEL 100 ppm TWA
PM Acetate	-	75 ppm STEL 50 ppm TWA	-	-	-	-	50 ppm TWA 270 mg/m ³ TWA	-	-	-

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol
Color	White
Odor	Aromatic
Odor threshold	Not available
pH	No data available

Melting point/range °C	No data available
Melting point/range °F	No data available
Boiling point/range °C	-44 °C
Boiling point/range °F	-47.2 °F
Flash point °C	-19
Flash point °F	-2.2
Evaporation rate	No data available
Flammability (Solid, Gas)	Extremely Flammable Aerosol
Lower explosion limit	1.5 %
Upper explosion limit	10.9 %
Vapor pressure	No data available
Vapor density	No data available
Relative density	.77 - .85
Solubility	Not available
Partition coefficient (n-octanol/water)	No data available
Autoignition temperature °C	Product is not self-igniting
Autoignition temperature °F	Product is not self-igniting
Decomposition temperature °C	No data available
Decomposition temperature °F	No data available
Viscosity	No data available

10. STABILITY AND REACTIVITY

Reactivity	Stable under normal conditions.
Chemical stability	Not established.
Possibility of hazardous reactions	None known.
Conditions to avoid	Do not puncture, incinerate or expose to temperatures above 120 degrees F. Exposure to temperatures above 120F may cause bursting.
Incompatible materials	No further relevant information available.
Hazardous decomposition products	None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation. Ingestion. Eyes. Dermal.

Symptoms

Dizziness. May cause eye irritation. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Propane	> 800000 ppm (Rat) 15 min	-	-
Toluene	= 12.5 mg/L (Rat) 4 h	= 12000 mg/kg (Rabbit) Dermal LD50 Rabbit 12000 mg/kg (Source: JAPAN_GHS)	= 2600 mg/kg (Rat) Oral LD50 Rat 2600 mg/kg (Source: JAPAN_GHS)
N-Butane	= 658 g/m ³ (Rat) 4 h	-	-
Titanium dioxide	-	-	> 10000 mg/kg (Rat)
Naphtha, petroleum, hydrotreated light	= 73680 ppm (Rat) 4 h	> 3160 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	> 5000 mg/kg (Rat) > 4300 mg/kg (Rat)
Calcium Carbonate	-	-	-
Isobutyl acetate	-	> 17400 mg/kg (Rabbit)	= 15400 mg/kg (Rat)
Mineral Spirits	> 5.2 mg/L (Rat) 4 h	> 2000 mg/kg (Rabbit)	> 5000 mg/kg (Rat)
Xylene (mix)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h > 5.04 mg/L (Rat) 4 h	> 1700 mg/kg (Rabbit) > 4350 mg/kg (Rabbit) > 2000 mg/kg (Rabbit)	= 3500 mg/kg (Rat) = 4820 mg/kg (Rat)
PM Acetate	-	> 5 g/kg (Rabbit)	= 8532 mg/kg (Rat)

ATEmix (dermal) Not available**ATEmix (oral)** Not available**ATEmix (inhalation-gas)** Not available**ATEmix (inhalation-vapor)** Not available**ATEmix (inhalation-dust/mist)** Not available**Carcinogenicity**

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA RTK Carcinogens	NTP
Propane	-	-	-	-
Toluene	A4	Group 3	-	-
N-Butane	-	-	-	-
Titanium dioxide	A4	Group 2B	Listed	-
Naphtha, petroleum, hydrotreated light	-	Group 3	-	-
Calcium Carbonate	-	-	-	-
Isobutyl acetate	-	-	-	-
Mineral Spirits	-	-	-	-
Xylene (mix)	A4	Group 3	-	-
PM Acetate	-	-	-	-

**Canadian Province
carcinogenicity limits**

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Propane	-	-	-	-	-	-
Toluene	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
N-Butane	-	-	-	-	-	-
Titanium dioxide	-	IARC 2B	ACGIH A4	ACGIH A4	ACGIH A4	-
Naphtha, petroleum, hydrotreated light	-	-	-	-	-	-
Calcium Carbonate	-	-	-	-	-	-
Isobutyl acetate	-	-	-	-	-	-
Mineral Spirits	-	-	-	-	-	-
Xylene (mix)	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
PM Acetate	-	-	-	-	-	-

12. ECOLOGICAL INFORMATION
Ecotoxicity

Chemical name	Algae/aquatic plants	Fish
Propane	-	-
Toluene	433: 96 h Pseudokirchneriella subcapitata mg/L EC50 12.5: 72 h Pseudokirchneriella subcapitata mg/L EC50 static	15.22 - 19.05: 96 h Pimephales promelas mg/L LC50 flow-through 12.6: 96 h Pimephales promelas mg/L LC50 static 5.89 - 7.81: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 14.1 - 17.16: 96 h Oncorhynchus mykiss mg/L LC50 static 5.8: 96 h Oncorhynchus mykiss mg/L LC50 semi-static 11.0 - 15.0: 96 h Lepomis macrochirus mg/L LC50 static 54: 96 h Oryzias latipes mg/L LC50 static 28.2: 96 h Poecilia reticulata mg/L LC50 semi-static 50.87 - 70.34: 96 h Poecilia reticulata mg/L LC50 static
N-Butane	-	-
Titanium dioxide	-	-
Naphtha, petroleum, hydrotreated light	-	258: 96 h Salmo gairdneri mg/L LC50 static
Calcium Carbonate	-	-
Isobutyl acetate	-	101: 48 h Leuciscus idus melanotus mg/L LC50 static 101 - 123: 48 h Leuciscus idus melanotus mg/L LC50 flow-through
Mineral Spirits	-	45: 96 h Pimephales promelas mg/L LC50 flow-through 2.2: 96 h Lepomis macrochirus mg/L LC50 static 2.4: 96 h Oncorhynchus mykiss mg/L LC50 static
Xylene (mix)	11: 72 h Pseudokirchneriella subcapitata mg/L EC50	13.4: 96 h Pimephales promelas mg/L LC50 flow-through 13.5 - 17.3: 96 h Oncorhynchus mykiss mg/L LC50 19: 96 h Lepomis macrochirus mg/L LC50 7.711 - 9.591: 96 h Lepomis macrochirus mg/L LC50 static 780: 96 h Cyprinus carpio mg/L LC50 semi-static 780: 96 h Cyprinus carpio mg/L LC50 13.1 - 16.5: 96 h Lepomis macrochirus mg/L LC50 flow-through 23.53 - 29.97: 96 h Pimephales promelas mg/L LC50 static 2.661 - 4.093: 96 h Oncorhynchus mykiss mg/L LC50 static 30.26 - 40.75: 96 h Poecilia reticulata mg/L LC50

Chemical name	Algae/aquatic plants	Fish
		static
PM Acetate	-	161: 96 h Pimephales promelas mg/L LC50 static

Persistence and degradability The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulation No information available

Chemical name	CAS-No	Partition coefficient (log Kow)
Propane 74-98-6	74-98-6	2.3 <=2.8
Toluene 108-88-3	108-88-3	2.7
N-Butane 106-97-8	106-97-8	2.89 <=2.8
Titanium dioxide 13463-67-7	13463-67-7	-
Naphtha, petroleum, hydrotreated light 64742-49-0	64742-49-0	-
Calcium Carbonate 1317-65-3	1317-65-3	-
Isobutyl acetate 110-19-0	110-19-0	1.72
Mineral Spirits 64742-47-8	64742-47-8	-
Xylene (mix) 1330-20-7	1330-20-7	2.77 - 3.15
PM Acetate 108-65-6	108-65-6	0.43

Mobility in soil Not available.

Other adverse effects No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Disposal information Dispose in accordance with federal, state, and local regulations. Controlled incineration is recommended for disposal of unused product. Prevent contamination of soil, drains and surface waters. Dispose of large containers to a licensed reconditioner. Dispose of small containers in compliance with local regulations. Do not puncture or incinerate. Do not heat or cut empty containers with electric or gas torches. Please recycle empty container whenever possible.

Contaminated packaging Dispose in accordance with local, state and federal regulations.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT

ID-No	UN1950
Proper shipping name	Aerosols, flammable
Hazard Class(es)	2.1
Subsidiary Risk	
Packing group	
Marine pollutant	No.

Special Provisions LTD QTY

TDG

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Packing group
Marine pollutant No.
Special Provisions LTD QTY

IATA

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Subsidiary Risk
Packing group
Special Provisions LTD QTY

IMDG/IMO

ID-No UN1950
Proper shipping name Aerosols
Hazard Class(es) 2
Packing group
EmS No F-D, S-U
Marine pollutant No
Special Provisions LTD QTY

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Propane	74-98-6	-	-	-
Toluene	108-88-3	-	-	-
N-Butane	106-97-8	-	-	-
Titanium dioxide	13463-67-7	-	-	-
Naphtha, petroleum, hydrotreated light	64742-49-0	-	-	-
Calcium Carbonate	1317-65-3	-	-	-
Isobutyl acetate	110-19-0	-	-	-
Mineral Spirits	64742-47-8	-	-	-
Xylene (mix)	1330-20-7	-	-	-
PM Acetate	108-65-6	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Propane	74-98-6	X	X	X
Toluene	108-88-3	X	X	X
N-Butane	106-97-8	X	X	X
Titanium dioxide	13463-67-7	X	X	X
Naphtha, petroleum, hydrotreated light	64742-49-0	X	X	X
Calcium Carbonate	1317-65-3	X	X	X
Isobutyl acetate	110-19-0	X	X	X
Mineral Spirits	64742-47-8	-	-	-
Xylene (mix)	1330-20-7	X	X	X
PM Acetate	108-65-6	-	-	-

California Prop. 65

WARNING: This product contains a chemical(s) known to the state of California to cause cancer, birth defects or other reproductive harm

Chemical name	CAS-No	California Prop. 65
Propane	74-98-6	-
Toluene	108-88-3	Developmental
N-Butane	106-97-8	-
Titanium dioxide	13463-67-7	Carcinogen
Naphtha, petroleum, hydrotreated light	64742-49-0	-
Calcium Carbonate	1317-65-3	-
Isobutyl acetate	110-19-0	-
Mineral Spirits	64742-47-8	-
Xylene (mix)	1330-20-7	-
PM Acetate	108-65-6	-

U.S. Federal Regulations**US EPA SARA 313**

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Propane	74-98-6	-	-
Toluene	108-88-3	1000 lb 454 kg 1 lb 0.454 kg	1.0 %
N-Butane	106-97-8	-	-
Titanium dioxide	13463-67-7	-	-
Naphtha, petroleum, hydrotreated light	64742-49-0	-	-
Calcium Carbonate	1317-65-3	-	-
Isobutyl acetate	110-19-0	5000 lb 2270 kg	-
Mineral Spirits	64742-47-8	-	-
Xylene (mix)	1330-20-7	100 lb 45.4 kg	1.0 %
PM Acetate	108-65-6	-	-

**US EPA SARA 311/312
hazardous categorization**

Not available

Chemical name	DSL/NDSL	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification
Propane	X	X	-
Toluene	X	X	-
N-Butane	X	X	-
Titanium dioxide	X	X	-
Naphtha, petroleum, hydrotreated light	X	X	-
Calcium Carbonate	X	X	-
Isobutyl acetate	X	X	-
Mineral Spirits	X	X	-
Xylene (mix)	X	X	-
PM Acetate	X	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health 1
 Flammability 3
 Instability 3

HMIS

Health 1
 Flammability 3
 Physical hazards 3

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 08-Jan-2019

Revision date 08-Jan-2019

Revision note

Key to abbreviations

ACGIH (American Conference of Governmental Industrial Hygienists)
 ATE (Average Toxicity Estimate)
 DSL/NDSL (Domestic Substance List/Non-Domestic Substance List)
 HMIS (Hazardous Materials Identification System)
 IARC (International Agency for Research on Cancer)
 IATA (International Air Transport Association)
 IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
 NFPA (National Fire Protection Association)
 NTP (National Toxicology Program)
 OEL (Occupational Exposure Level)
 OSHA (Occupational Safety and Health Administration of the US Department of Labor)
 PEL (Permissible Exposure Limit)
 TSCA (Toxic Substance Control Act)
 USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet