

MATERIAL SAFETY DATA SHEET

NFPA RATING: Health = 1 Flammability = 1 Reactivity = 0
 HMIS RATING: Health = 1 Flammability = 1 Reactivity = 0

SECTION I -- IDENTITY AND MANUFACTURER'S INFORMATION (445N-60A)

Manufacturer's Name: HILLYARD INDUSTRIES **Product Name:** SUPER HIL-TONE
Address: 302 North Fourth Street **Date Prepared:** March 18, 1996
 St. Joseph, MO 64501 **Prepared by:** Regulatory Affairs Department
Emergency Telephone No.: (800)-424-9300 (Only in the event of chemical emergency involving a spill, leak, fire, exposure or accident involving chemicals.) **Other information calls:** (816) 233-1321 (Ext. 8285)
<http://www.hillyard.com>

SECTION II -- INGREDIENTS/IDENTITY INFORMATION

Components

(Specific Chemical Identity: Common Name(s))	CAS#	OSHA PEL	ACGIH TLV	OTHER LIMITS RECOMMENDED	%
Petroleum distillate (solvent-refined heavy and light paraffinic)	64741-88-4 & 64741-89-5	5 mg/M ³	5 mg/M ³	10 mg/M ³	94-99
Aliphatic hydrocarbon petroleum naphtha	64742-88-7	100 ppm*	100 ppm*	not applicable	less than 5%

VOC = Less than 7%.

*Not established for this CAS #, use Stoddard Solvent (CAS #8052-41-3) for PEL & TLV.

SECTION III -- PHYSICAL / CHEMICAL CHARACTERISTICS

Boiling Point: 305°F **Specific Gravity (H₂O = 1): 25°C =** 0.86 **39°C =** 0.85
Vapor Pressure (mm Hg.): 6.6 **Percent Volatile by Volume (%):** 6
Vapor Density (AIR = 1): 4.7 **Evaporation Rate (ethyl ether = 1):** slower than 1
Solubility in Water: negligible **Appearance and Odor:** slightly yellow - transparent liquid; pleasant odor
Auto-Ignition: 243°C.

SECTION IV -- FIRE AND EXPLOSION HAZARD DATA

Flash point: 225°F (Pensky-Marten Closed Cup) **Flammable Limits:** LEL = not established UEL = not established
Extinguishing Media: Use water spray, regular foam, CO₂ or carbon dioxide fire fighting apparatus.
Special Fire Fighting Procedures: The use of self-contained breathing apparatus is recommended for fire fighters. Wear structural firefighters protective clothing.
Unusual Fire and Explosion Hazards: Can be made to burn (flash point 225°F). Incomplete combustion can yield carbon monoxide and various hydrocarbons.

SECTION V -- PHYSICAL HAZARDS

Stability: Stable **Conditions to Avoid:** None known
Incompatibility (Materials to Avoid): This product is not compatible with strong oxidizing agents, strong acids or bases and selected amines.
Hazardous Decomposition Products or Byproducts: Thermal decomposition in air produces carbon monoxide and carbon dioxide.
Hazardous Polymerization: Will not occur **Conditions to Avoid:** None known

SECTION VI -- HEALTH HAZARD DATA

Routes of entry: Inhalation? Yes Skin? Yes Ingestion? Yes

HEALTH HAZARDS (1. Acute and 2. Chronic)

- When tested according to Federal Hazardous Substance Act product was not a primary skin irritant but produced moderate skin irritation on prolonged exposure and the concentrate was not an eye irritant. Also test on the concentrate showed that acute oral LD50 was not acutely toxic at 5.0 g./kg. Inhalation testing showed that the LC50 nominal concentration to be 13.2 mg./l. (actual concentration 3.8 mg./l. Prolonged overexposure by inhalation may cause headache, dizziness, nausea, unconsciousness.
- None known by manufacturer.

Chemical listed as Carcinogen or Potential Carcinogen:

National Toxicology Program = No **I.A.R.C. Monographs =** No **OSHA =** No

This product has no carcinogens listed by IARC, NTP, NIOSH, or ACGIH as of this date, greater than or equal to 0.1%.

SECTION VI -- HEALTH HAZARD DATA cont.

Signs and Symptoms of Exposure: Ingestion may irritate stomach and intestines. May be aspirated into lungs if swallowed, resulting in pulmonary edema and chemical pneumonitis.

Medical Conditions Generally Aggravated by Exposure: Pre-existing eye, skin and respiratory disorders. Isoparaffinic hydrocarbons have caused kidney injury in male rats only. No comparable health hazard for kidney disease is known to occur in humans.

Emergency and First Aid Procedures: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately. In case of eye contact immediately flush with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If irritation persists get medical attention. Wash clothing before reuse. If swallowed, do not induce vomiting. Call a physician.

SECTION VII -- PRECAUTIONS FOR SAFE HANDLING AND USE

Steps To Be Taken In Case Material Is Released Or Spilled:

Remove all sources of ignition. Avoid breathing vapors or spray mist. Ventilate area and remove with inert absorbent. Do not pick up solution with automatic scrubber or wet pick-up vacuum.

Waste Disposal Method: Dispose of in accordance with state or local regulations. Do not incinerate closed container. Do not dispose of in storm drains or waterways.

Precautions To Be Taken In Handling And Storing: Since empty packages retain product residue, follow label warnings even after package is empty. Keep container closed when not in use.

Other Precautions: Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. USE ONLY WITH ADEQUATE VENTILATION. Do not breathe vapors or spray mist. **Ensure fresh air entry during application and drying.** If you experience eye watering, headache or dizziness or if air monitoring demonstrates vapor / mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH/MSHA approved) during and after application. Follow respirator manufacturer's directions for respirator use. Do not spray fine fog mist into sparks or open flame - vapors may ignite. Close container after each use. Avoid prolonged contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally. This product contains no reportable quantities of toxic chemicals subject to reporting requirements of Section 313 of SARA Title III Emergency Planning and Community Right to Know Act of 1986 and of 40 CFR Part 372.

SECTION VIII -- CONTROL MEASURES:

Respiratory Protection (Specify Type): Usually not needed unless product is misted or heated. Wear appropriate, properly fitted respirator (NIOSH or MSHA approved) unless air monitoring demonstrates vapor or mist levels are above applicable limits.

Ventilation: At least 10 air changes/hour recommended

Local Exhaust = Recommended **Mechanical (General) =** Recommended **Special =** N/A **Other =** N/A

Protective Gloves: Not necessary with normal use. If prolonged contact is unavoidable, wear polyvinyl chloride (PVC); neoprene; nitrile; polyvinyl alcohol; viton.

Eye Protection: Not necessary with normal use.

Other Protective Clothing or Equipment: Normal use - Protective clothing such as uniforms, coveralls. If prolonged contact is unavoidable, wear protective clothing made of the polyvinyl alcohol (PVA); polyvinyl chloride (PVC); neoprene; nitrile; viton; polyurethane.

Work / Hygienic Practices: Wash contaminated clothing before reuse.

SECTION IX - TRANSPORTATION INFORMATION

Applicable regulations: CFR = no IMCO = no IATA = no.

Proper shipping name for highway: Petroleum Oil

UN No.: not applicable **Limited Qty.:** not applicable **Hazard class:** not applicable

Labels required: not required **DOT Exception:** not applicable

EPA Hazardous waste characteristics: **Ignitability** = not applicable; **Corrosivity** = not applicable;

Reactivity = not applicable.

DISCLAIMER OF WARRANTIES

NO REPRESENTATIONS OR WARRANTIES, EITHER EXPRESS OR IMPLIED, OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR OF ANY NATURE ARE MADE WITH RESPECT TO THE PRODUCT(S) OR INFORMATION CONTAINED IN THIS MATERIAL SAFETY DATA SHEET.

The information and recommendations contained in this Material Safety Data Sheet are supplied pursuant to 29 CFR 1910.1200 of the Occupational Safety and Health Standards Hazard Communication Rule. All information contained herein is presented in good faith and is believed to be appropriate and accurate.

THE BUYER OR USER ASSUMES ALL RISKS ASSOCIATED WITH THE USE, MISUSE OR DISPOSAL OF THIS PRODUCT. THE BUYER OR USER IS RESPONSIBLE TO COMPLY WITH ALL FEDERAL, STATE OR LOCAL REGULATIONS CONCERNING THE USE, MISUSE OR DISPOSAL OF THESE PRODUCTS.